



Kategorija: **RUTERI I EKSTENDERI**

Šifra: **12922**

Proizvođač: **TENDA**

**Tenda MW3 \* AC1200 dual band distribution mesh WiFi system 200m2 2PACKS**



**Maloprodajna cena: 9.290,00 RSD**

**Web cena: 7.910,00 RSD**

**Ušteda: 1.380,00 RSD**

## Specifikacija

MW3 is a 1200Mbps dual band distribution mesh WiFi system designed for 100-300? houses, bringing you with whole home WiFi coverage, as well as fast and stable internet connection. Pack of 3 provides you with up to 300? WiFi range; while pack of 2 provides you with up to 200? WiFi range. Compliant with IEEE 802.11v and IEEE 802.11r seamless roaming protocols, MW3 supports automatic network optimization and automatic routing selection, allowing you to enjoy more stable and flexible wireless network.

Standard&Protocol: IEEE802.3, IEEE802.3u

Interface: 2 Ethernet ports per mesh node

WAN and LAN on primary mesh node

Both act as LAN ports on additional mesh nodes

Antenna: 2\*3dBi internal dual band antennas

Button: 1 reset button

Power: Input:100-240V—50/60Hz

Dimension: 90 x 90 x 90mm

Wireless Standards: IEEE 802.11ac/a/n 5GHz

IEEE 802.11b/g/n 2.4GHz

Wireless Frequency2.4G: 2400MHz-2483MHz

5G: 5150MHz-5250MHz or 5725MHz-5825MHz

Data Rate: 5GHz: Up to 867Mbps

2.4GHz: Up to 300Mbps

Frequency: Simultaneous dual band 2.4GHz & 5GHz

Basic Features:SSID Broadcast

Beamforming

Wireless Security: Mixed WPA/WPA2-PSK(default)
Wireless roaming: Comply with IEEE802.11v/r
Internet Connection Type: PPPoE, Dynamic IP, Static IP, Bridge Mode
DHCP ServerDHCP Server
DHCP Client List
Virtual Server: Port Forwarding
UPnP
QoS: Support Smart QoS
Firewall: Forbid UDP flood attack
Forbid TCP flood attack
Forbid ICMP flood attack
DNS: Support manually setting DNS server
VPN: IPsec pass through
PPTP pass through
L2TP pass through
Other: Parental Control
Guest Network
Firmware upgrade online
Reset to factory settings
Setup Requirements: A mobile device running Android 4.0+ or iOS 8+
Temperature: Operating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?.
Humidity: Operating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Certification: FCC, CE, RoHS, EAC, IC
Package Content: (2-pack) 2 identical mesh nodes
2 power adapters
Quick install guide
1 ethernet cable

Raspoloživost robe možete proveriti pozivanjem Call Centra na 069/853-90-69

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.