



Kategorija: **MATIČNE PLOČE ZA AMD
SOKET**

Šifra: **19882**

Matična ploča AM4 Gigabyte A520M H

Proizvođač: **GIGABYTE**

**Matična ploča AM4 Gigabyte A520M
H**

**Maloprodajna cena: 7.780,00
RSD**

Web cena: 6.720,00 RSD

Ušteda: 1.060,00 RSD

Specifikacija

| | |
|------------------------------------|--|
| Tip procesora | AMD |
| Podnožje | AMD® AM4 |
| Čipset | AMD® A520 |
| Format ploče | Micro ATX |
| Podržani procesori | AMD Socket AM4, support for: AMD Ryzen™ 5000 Series Ryzen™ 5000 G-Series Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors |
| Podržana memorija | DDR4 |
| Memorija | 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Support for DDR4 5100(O.C.) 4800(O.C.) 4600(O.C.) 4400(O.C.) 4266(O.C.) 4133(O.C.) 4000(O.C.) 3866(O.C.) 3733(O.C.) 3600(O.C.) 3466(O.C.) 3400(O.C.) 3200 2933 2667 2400 2133 MHz memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx82Rx8 memory modules* * ECC memory (ECC mode) support varies by CPU Support for non-ECC Un-buffered DIMM 1Rx82Rx81Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules |
| Slotovi za proširenje | CPU: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16 Chipset: 2 x PCI Express x1 slots, supporting PCIe 3.0 |
| Storage | CPU: 1 x M.2 connector (Socket 3, M key, type 224222602280 SATA and PCIe 3.0 x4x2 SSD support) Chipset: 4 x SATA 6Gbs connectors Support for RAID 0, RAID 1, and RAID 10 |
| Mrežna karta | Realtek® GbE LAN chip (1 Gbit100 Mbit) |
| Zvučna karta | Realtek® Audio CODEC High Definition Audio 245.17.1-channel |
| USB | CPU: 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 2 x USB 3.2 Gen 1 ports available through the internal USB header 6 x USB 2.01.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers) |
| Konektori na zadnjoj strani | 1 x PS2 keyboardmouse port 1 x DVI-D port 1 x HDMI port 4 x USB 3.2 Gen 1 ports 2 x USB 2.01.1 ports 1 x Q-Flash Plus button 1 x RJ-45 port 3 x audio jacks |
| Interni konektori | 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 2 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header 1 x M.2 Socket 3 connector 4 x SATA 6Gbs connectors 1 x front panel header 1 x front panel audio header 1 x speaker header 1 x USB 3.2 Gen 1 header 2 x USB 2.01.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x serial port header 1 x chassis intrusion header 1 x Clear CMOS jumper |
| Bios | 1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0 |
| Razno | {"url":"","title":"","target":""} |

Raspoloživost robe možete proveriti pozivanjem Call Centra na 069/853-90-69

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.