



Firma: STD Comp
Adresa: Vojvode Putnika 51
Telefon: 069/853-90-69
Fax:
PIB: 111971285
E-mail: stdcomp015@gmail.com

Matična ploča AM4 Gigabyte B550 AORUS ELITE V2



No Image Available

Šifra: 19993

Kategorija proizvoda: MATIČNE PLOČE ZA AMD SOKET

Proizvođač: GIGABYTE

Cena: **15.660,00** rsd.

Tip procesora:	AMD
Podnožje:	AMD® AM4
Čipset:	AMD® B550
Format ploče:	ATX
Podržani procesori:	AMD Ryzen™ 5000 Series Ryzen™ 5000 G-Series Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors
Podržana memorija:	DDR4
Memorija:	Maksimalna ukupna memorija: 128GB Podržane memorije: 2.133MHz, 2.400MHz, 2.667MHz, 2.933MHz, 3.200MHz, 3.300Mhz (O.C.), 3.333Mhz (O.C.), 3.400Mhz (O.C.), 3.466Mhz (O.C.), 3.600Mhz (O.C.), 3.733Mhz (O.C.), 3.800Mhz (O.C.), 3.866Mhz (O.C.), 4.000Mhz (O.C.), 4.400Mhz (O.C.), 4.733Mhz (O.C.)
Slotovi za proširenje:	1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: - AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support PCIe 4.0 x16 mode - AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support PCIe 3.0 x16 mode * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot. 1 x PCI Express x16 slot (PCIEX2), integrated in the Chipset: - Supporting PCIe 3.0 x2 mode 1 x PCI Express x16 slot (PCIEX1_2), integrated in the Chipset: - Supporting PCIe 3.0 x1 mode 1 x PCI Express x1 slot (PCIEX1_1), integrated in the Chipset: - Supporting PCIe 3.0 x1 mode
Storage:	1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type

22422260228022110 SSDs: -
AMD Ryzen™ 5000 Series and
Ryzen™ 3000 Series Processors
support SATA and PCIe 4.0 x4x2
SSDs - AMD Ryzen™ Ryzen™
5000 G-Series and Ryzen™ 4000
G-Series Processors support
SATA and PCIe 3.0 x4x2 SSDs 1 x
M.2 connector (M2B_SB),
integrated in the Chipset,
supporting Socket 3, M key, type
22422260228022110 SSDs: -
Supporting SATA and PCIe 3.0
x4x2 SSDs 4 x SATA 6Gbs
connectors, integrated in the
Chipset: - Support for RAID 0,
RAID 1, and RAID 10

Mrežna karta:	Realtek® 2.5GbE LAN chip (2.5 Gbit1 Gbit100 Mbit)
Zvučna karta:	Realtek® ALC1200 codec High Definition Audio 245.17.1- channel Support for SPDIF Out
USB:	CPU: 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel 2 x USB 3.2 Gen 1 ports on the back panel Chipset: 1 x USB Type-C™ port with USB 3.2 Gen 1 support, available through the internal USB header 1 x USB 3.2 Gen 1 port on the back panel 2 x USB 3.2 Gen 1 ports available through the internal USB header 2 x USB 2.01.1 ports on the back panel Chipset+USB 2.0 Hub: 4 x USB 2.01.1 ports available through the internal USB headers
Konektori na zadnjoj strani:	1 x DisplayPort 1 x HDMI port 2 x USB 3.2 Gen 2 Type-A ports (red) 3 x USB 3.2 Gen 1 ports 2 x USB 2.01.1 ports 1 x Q-Flash Plus button 1 x RJ-45 port 1 x optical SPDIF Out connector 5 x audio jacks
Interni konektori:	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 2 x M.2 Socket 3 connectors 4 x SATA 6Gbs connectors 1 x CPU fan header 1 x water cooling CPU fan header 3 x system fan headers 1 x CPU cooler LED stripRGB LED strip header 2 x addressable LED strip headers 2 x RGB LED strip headers 1 x front panel header 1 x front panel audio header 1 x USB Type-C™ port, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.01.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC- TPM2.0_S module only) 1 x Clear CMOS jumper
Bios:	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0