



Kategorija: **UPS**

Šifra: **5183**

Proizvođač: **APC**

UPS APC SMT1500RM12UC 1500VA



Maloprodajna cena: 149.480,00 RSD

Web cena: 131.750,00 RSD

Ušteda: 17.730,00 RSD

Specifikacija

SMT1500RM12UC, Izlazna snaga 1000 W, Tehnologija Line interactive AVR, Pure sinewave, Izlazni napon 230 V, Ulazni napon 230 V, Vreme punjenja 3 h, Vreme rada (50% load) 25,8 min, Vreme rada (100% load) 7,2 min, Komunikacija Smart Slot, USB. SmartConnect

APC Smart-UPS 1500VA LCD RM 2U 230V with SmartConnect

Cold-start capable

Provides temporary battery power when the utility power is out.

Energy meter

Provides actual kilowatt hours of usage for energy conscious users.

Green mode

Patent-pending operating mode that bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection.

High online efficiency

Reduces utility costs, generates less heat.

Intuitive LCD interface

Provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys.

Predictive replace battery date

Dynamically provides the month and year when battery replacement is recommended to aide in long term maintenance planning.

Pure sine wave output on battery

Simulates utility power to provide the highest degree of compatibility for active PFC (power factor corrected) servers and sensitive electronics.

Single switched outlet group

Single outlet group that may be controlled separately from the UPS for discrete reboot of hung devices, sequenced onoff and non-critical load shedding.

SmartConnect

Innovative, easy to use remote monitoring feature that provides automatic notifications, firmware updates, and advanced support services.

SmartSlot

Customize UPS capabilities with management cards.

Temperature-compensated battery charging

Prolongs battery life by regulating the charge voltage according to battery temperature.

Izlazna snaga [W]	1000
Tehnologija	Line interactive AVR, Pure sinewave
Izlazni napon [V]	230
Promena izlaznog napona [%]	0
Izlazni priključci	IEC 320 C13
Ulazni napon [V]	230
Ulazna frekvencija	0
Podesivost ulaznog napona [V]	0
Vreme punjenja [h]	3
Vreme rada (50% load) [min]	25.8
Vreme rada (100% load) [min]	7.2
Surge rating [J]	459
Komunikacija	RJ-45 Port, DB-9 RS-232, Smart Slot, USB

Raspoloživost robe možete proveriti pozivanjem Call Centra na 069/853-90-69

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.